



电驱越野剪叉平台

Electric drive off-road platform

SJPT1212RT

- 全地形、全路面行驶。
All-terrain, all-road driving.
- 越野轮胎，大离地间隙，通过性好。
Off-road tires, high ground clearance, good passability.
- 交流电机驱动，效率高、扭矩大、寿命长。
Ac motor drive, high efficiency, large torque, long life.
- 纯电设计，无噪音，零排放等优势，大容量电池，持久耐用。
Pure electric design, no noise, zero emission and other advantages, large capacity battery, durable.
- 屏显人机交互，参数设置、故障诊断，参数读写，系统监控。
Screen display man-machine interaction, parameter setting, fault diagnosis, parameter reading and writing, system monitoring.
- 支腿一键调平，安全可靠省心。
automatic leveling, safe, reliable and worry free.



产品配置

Machine Parameters

动作蜂鸣 Action buzzer	工作时间表 Working hours table	自动刹车系统 ABS
折叠围栏 Folding fence	工作频闪灯 Working strobe light	紧急停止按钮 Emergency button
免维护电池 Maintenance-free battery	平台自锁门 Self-locking door	故障诊断系统 Fault diagnosis system
安全检修支撑 Safety maintenance support	紧急下降系统 Emergency descent system	支腿自动调平 Tilt protection system
充电保护系统 Charge protection system	单向延伸平台 Unidirectional extension platform	倾斜保护系统 Tilt protection system
浮动后桥 Floating rear axle	越野实心轮胎 Off-road solid tires	后轮自动差速 Rear wheel automatic differential speed

河南通和智能机械设备有限公司

Henan Tonghe Intelligent Mechanical Equipment Co., Ltd

地址：长葛市未来路 电话：0374-6608000

手机：18837418333 邮箱：hntonghe@163.com



型号Model no.	SJPT1212RT	
1	最大工作高度 Max. working height	14m
2	A最大平台高度 Max. platform height	12m
3	B最小平台高度 Min. platform height	1530mm
4	C工作平台长度 Work platform length	2570mm
5	D工作平台宽度 Work platform width	1380mm
6	平台延伸尺寸 Platform extension size	1200mm
7	E整机高度(护栏升起) Whole machine height(Fence expansion)	2650mm
8	整机高度(护栏折叠) Whole machine height(Fence folded)	2100mm
9	F整机长度 Whole machine length	3320mm
10	G整机宽度 Whole machine width	1800mm
11	额定载荷 Rated load	350kg
12	延伸平台安全工作载荷 Extended platform safe	113kg
13	最大工作人数 Max. workers	3
14	最小离地间隙 Min. ground clearance	300mm
15	行驶速度(收藏状态) Driving speed(folded mode)	6.5Km/h
16	行驶速度(起升状态) Driving speed(lifting)	-
17	起升电机 Lifting motor	48V/4.5KW/4.5CC
18	驱动电机 Driving motor	48V/3.5KW*2
19	上升/下降时间 Lifting/falling time	62/42s
20	最大爬坡能力 Max. climbing capacity	30%
21	最大工作角度 Max. operating angle	1.5° / 3°
22	行走方式 Driving mode	实心越野轮胎 solid off-road tire
23	车轮规格 Wheel size	26×12-16
24	蓄电池 Storage battery	8×12V/150Ah选配 48V320Ah(Li)
25	充电器 Battery charger	48V/30A 48V/35A (Li)
26	整机重量 Whole machine weight	3740kg

