



## 履带电驱剪叉平台

Crawler electric drive scissor platform

### SJPT0607T

- 整车的运输方便性、整车通过性高。  
Transport is convenient and pass through is high.
- 整车维修方便，日常检查及维护保养便捷。  
Daily inspection and maintenance is convenient.
- 人机交互，故障诊断，参数读写，系统监控。  
Man-machine interaction, fault diagnosis, parameter reading and writin, system monitoring.
- 新能源动力，体积小、重量轻、无污染  
New energy power, small size, light weight, non-pollution.
- 可随意进入载人电梯，专为楼宇夹层登高作业量身打造。  
Can enter the elevator at will, specially designed for building mezzanine climbing operation.
- 交流电机，效率高、扭矩大、寿命长。  
Ac motor, high efficiency, large torque, long life.



### 产品配置

#### Machine Parameters

动作蜂鸣 Action buzzer	工作时间表 Working hours table	自动刹车系统 ABS
折叠围栏 Folding fence	工作频闪灯 Working strobe light	紧急停止按钮 Emergency button
免维护电池 Maintenance-free battery	平台自锁门 Self-locking door	故障诊断系统 Fault diagnosis system
安全检修支撑 Safety maintenance support	紧急下降系统 Emergency descent system	倾斜保护系统 Tilt protection system
充电保护系统 Charge protection system	单向延伸平台 Unidirectional extension platform	

河南通和智能机械设备有限公司

Henan Tonghe Intelligent Mechanical Equipment Co., Ltd

地址：长葛市未来路 电话：0374-6608000

手机：18837418333 邮箱：hntonghe@163.com



型号Model no.		SJPT0407T	SJPT0607T
1	最大工作高度 Max. working height	6m	8m
2	A最大平台高度 Max. platform height	4m	6m
3	B最小平台高度 Min. platform height	950mm	1030mm
4	C工作平台长度 Work platform length	1400mm	1400mm
5	D工作平台宽度 Work platform width	760mm	760mm
6	平台延伸尺寸 Platform extension size	600mm	600mm
7	E整机高度(护栏升起) Whole machine height (Fence expansion)	1950mm	2130mm
8	整机高度(护栏折叠) Whole machine height (Fence folded)	1560mm	1740mm
9	F整机长度 Whole machine length	1520mm	1520mm
10	G整机宽度 Whole machine width	880mm	880mm
11	额定载荷 Rated load	230kg	230kg
12	延伸平台安全工作载荷 Extended platform safe working load	100kg	100kg
13	最大工作人数 Max. workers	2	2
14	行驶速度(收藏状态) Driving speed (folded mode)	2.5Km/h	2.5Km/h
15	行驶速度(起升状态) Driving speed (lifting)	0.45Km/h	0.45Km/h
16	起升电机 Lifting motor	24V/2.2KW2.6CC	24V/2.2KW2.6CC
17	驱动电机 Driving motor	24V/2×1KW	24V/2×1KW
18	上升/下降时间 Lifting/falling time	36/37s	36/37s
19	最大爬坡能力 Max. climbing capacity	30%(17°)	30%(17°)
20	最大工作角度 Max. operating angle	1.5° / 2.5°	1.5° / 2.5°
21	驱动/制动 Drive/brake	双后轮 dual rear-wheels	双后轮 dual rear-wheels
22	行走方式 Driving mode	橡胶履带 rubber track	橡胶履带 rubber track
23	车轮规格 Wheel size	150/72/42	150/72/42
24	蓄电池 Storage battery	2×12V120Ah	2×12V120Ah
25	充电器 Battery charger	24V20A	24V20A
26	整机重量 Whole machine weight	816kg	980kg

